

You asked, we listened! Our Dual Switch Technology is now available in the Strion DS HL for maximum illumination with a wide beam.



**700
LUMENS**



TEN-TAP® Programming - Select one of three different programs:

- 1.) High/medium/low with strobe;
- 2.) High only without strobe;
- 3.) High/medium/low without strobe

Four operating modes:

- High for a bright super-bright beam: 700 lumens; 12,000 candela; 219m beam; runs 1.25 hours
- Medium for bright light and longer run time: 300 lumens; 5,000 candela; 141m beam; runs 3.25 hours
- Low provides a less intense beam and extended run time: 40 lumens; 800 candela; 57m beam; runs 20 hours
- Strobe for disorienting or signaling: runs 2.5 hours

Optimized electronics provide regulated intensity

Gasket sealed, Borofloat high temperature glass lens

IPX4 water resistant; 2m impact resistance tested

Serialized for positive identification

6.33 in. (16.08 cm); 5.4 oz (153 grams)

Limited Lifetime Warranty

Visit www.streamlight.com for full warranty information

See reverse for system configurations

Item #	Item Description
74621	Strion DS HL - IEC Type A (120V/100V) AC/12V DC – 1 holder Clam packaged
74620	Strion DS HL with Grip Ring - IEC Type A (120V/100V) AC
74619	Strion DS HL - IEC Type A (120V/100V)/12V DC PiggyBack
74618	Strion DS HL - IEC Type G (240V) AC/12V DC – 1 holder
74617	Strion DS HL - IEC Type C (230V) AC
74616	Strion DS HL - IEC Type C (230V) AC/12V DC – 2 holders
74615	Strion DS HL - IEC Type C (230V) AC/12V DC – 1 holder
74614	Strion DS HL - 12V DC
74613	Strion DS HL - IEC Type A (120V/100V) AC
74612	Strion DS HL - IEC Type A (120V/100V) AC/12V DC – 2 holders
74611	Strion DS HL - IEC Type A (120V/100V) AC/12V DC – 1 holder
74610	Strion DS HL (WITHOUT CHARGER)

