

## ProTac® HL-X

### DUAL FUEL - LITHIUM ION RECHARGEABLE or 2X CR123 FLASHLIGHT

**MARKET**

**APPLICATIONS:** Professional Light - Hardware/Tool, Industrial, Law Enforcement, Security, Automotive, Sporting Goods, Consumer.

**DESCRIPTION:**

The ProTac® HL-X is a 1000 lumen tactical light and incorporates the versatility to use two battery types; two CR123A batteries, or one Streamlight Rechargeable Li Ion cell (see Battery detail below). Multi battery versatility means you can always use primary disposable cells to power the light if your rechargeable cell is out of power and a charging source is not available. Designed for use in all markets, it features a tactical tail cap switch for momentary or constant on operation, three different user selectable programs and a pocket clip for convenience. The aluminum housing with Type II Military Spec anodizing helps make the light extremely durable and abrasion resistant. Packaged with a removable pocket clip and holster. Available in Black.

**CASE MATERIAL:** 6000 series machined aircraft aluminum with Type II MIL-Spec anodized finish. Available in Black.

**DIMENSIONS:** Length: 5.43 in. (13.8 cm) Head Diameter: 1.44 in. (3.7 cm) Body Diameter: 1.0 in. (2.54 cm)

**WEIGHT:**  
5.7 oz (162 grams) with 2X CR123  
6.2 oz (176 grams) with Li Ion rechargeable battery. (not included in purchase)

**LENS:** AR Coated Glass lens; gasket sealed.

**LIGHT SOURCE:** C4® LED technology, impervious to shock with a 50,000 hour lifetime.

**LIGHT OUTPUT:** See chart. Fully regulated output for consistent lumen performance over the battery life.

**ON/OFF:** Multi-function, push-button tactical tail switch. One handed operation of momentary, variable intensity or strobe mode. TEN-TAP® programmable switch allows user selection of one of three different programs: high/strobe/low (factory default), high only, or low/medium/high.

**RUN TIME:** See Chart. All runtime claims are to 10% of initial lumen output. Strobe: 2.5 continuous hours.

**BATTERY:** Two (2) 3 Volt CR123A Lithium batteries, (CR123A batteries have a shelf life of 10 years)  
One Streamlight Li Ion 18650 protected cylindrical 3.7V 2600 mAh rechargeable battery that has its own cradle charging system. (Optional)









**FEATURES:**


C4® LED technology for extreme brightness.  
IPX7 rated for water resistant operation. All openings o-ring sealed.  
2 meter impact resistance tested.  
LED Solid State Power Regulation provides maximum light output throughout battery life.  
TEN-TAP® programmable switch allows user to select one of three different programs.  
Anti-roll face cap.  
Serialized for positive identification.  
Removable pocket clip and Holster

**APPROVALS:**  Meets applicable European Community Directives.

**WARRANTY:** Streamlight's Limited Lifetime Warranty

**OPTIONAL ACCESSORIES:** None

	WITH CR123A BATTERIES				WITH 18650 RECHARGEABLE BATTERY			
	FL1 STANDARD	HIGH	MEDIUM	LOW	FL1 STANDARD	HIGH	MEDIUM	LOW
<b>OUTPUT</b>		1000 LUMENS	400 LUMENS	65 LUMENS		1000 LUMENS	400 LUMENS	65 LUMENS
<b>RUNTIME</b>		1h 15min	3h	20h		1h 30min	3h 30m	23h
<b>DISTANCE</b>		330m	200m	80m		330m	200m	80m
<b>INTENSITY</b>		27,100cd	10,000cd	1,600cd		27,100cd	10,000cd	1,600cd
	Strobe Run Time: 2 Hr 30 Min				Strobe Run Time: 3 Hr 15 Min			

