

**STINGER LED HL®/ STINGER DS LED HL®  
HIGH LUMEN RECHARGEABLE FLASHLIGHT**

**MARKET APPLICATIONS:** Law Enforcement, Sporting Goods, Security, Fire & Rescue, Hardware/Tool, Automotive, Industrial, Consumer

**DESCRIPTION:** Compact & extremely powerful, the Stinger LED HL® and Stinger DS LED HL® rechargeable flashlights offer 3 microprocessor controlled intensity modes, strobe mode and the latest in high power LED technology. The Stinger DS LED HL® includes a second independent easy to locate tactical tailcap switch. The combination of rechargeable batteries and the C4® LED results in one of the lowest operating costs of any flashlight made.

**CASE MATERIAL:** 6000 series machined aircraft aluminum with non-slip rubberized comfort grip with anti-roll rubber ring.

**DIMENSIONS:** Stinger LED HL® Length: 8.41 in. (21.36 cm)      Diameter: Major Diameter: 1.62 in. (4.11 cm)  
Stinger DS LED HL® Length: 8.85 in. (22.48 cm)      Body Diameter: 1.17 in. (2.97 cm)

**WEIGHT:** Stinger LED HL®: 12.4 oz (352 grams)\*      Stinger DS LED HL®: 12.8 oz (364 grams)\*


**LENS:** Unbreakable polycarbonate with scratch-resistant coating. O-ring sealed.

**LIGHT SOURCE:** C4® LED technology, impervious to shock with a 50,000 hour lifetime.

**LIGHT OUTPUT:** See Chart. Optimized electronics provides regulated intensity.  
Deep-dish parabolic reflector produces a concentrated beam with optimum peripheral illumination.



**ON/OFF:** Multi-function, easy access head mounted push-button switch designed for extremely long life; tested at 1 million actuations. Stinger DS LED HL® provides a second multi-function push-button tactical tailswitch where both switches offer full feature control independent of each other.

**RUN TIME:**  See Chart. Strobe: 3 continuous hours.

**BATTERY:** 3-cell, 3.6 Volt, 2.6Ahr Ni-MH sub-C battery, rechargeable up to 1000 times.



**CHARGE HOLDERS:** Fits existing Stinger® chargers and new Smart chargers.  
Steady charger: Fully recharges within 16 hours.  
Smart charger: Fully recharges within 4.5 hours (5V/1A USB input) or 3 hours (12VDC input).  
Smart PB charger: Fully recharges within 7.5 hours (5V/1A USB input) or 4 hours (12VDC input).

**CHARGE CORDS:** Streamlight universal AC input voltage, 5V/1A USB or 12.7V/.8A output charge cords available with IEC Type A (US & Japan), Type C (Euro) or Type G (UK) plugs. 5V USB also available with IEC Type I (Australia) plug.





**FEATURES:** C4® LED technology for extreme brightness.  
IPX4 Rated for water resistant operation.  
1 meter impact resistance tested.  
Serialized for positive identification.  
LED Charge-continuity indicator on charger base.  
Compact, snap-in charger mounts in any position.




**WARRANTY:** Streamlight's Limited Lifetime Warranty.

**APPROVALS:**  Meets applicable European Community Directives.  
 CEC Compliant (Smart charger models only)

**OPTIONAL ACCESSORIES:** Safety wands, ring holder, holster, color filters, 5-unit bank charger, Smart charger, Steady charger or Smart Piggy-Back® charger that allows for simultaneous charging of light and battery.

	FL1 STANDARD	HIGH	MEDIUM	LOW
OUTPUT		<b>800</b> LUMENS	<b>400</b> LUMENS	<b>200</b> LUMENS
RUN TIME		<b>1h 30min</b>	<b>2h 30min</b>	<b>5h</b>
DISTANCE		<b>310m</b>	<b>219m</b>	<b>155m</b>
INTENSITY		<b>24,000cd</b>	<b>12,000cd</b>	<b>6,000cd</b>



\* With battery (included in purchase)