



MICROSTREAM USB®
LITHIUM ION RECHARGEABLE FLASHLIGHT

MARKET

APPLICATIONS: Professional Light - Hardware/Tool, Industrial, Law Enforcement, Security, Automotive, Sporting Goods, Consumer.

DESCRIPTION: The Microstream® USB is a compact Lithium ion battery powered flashlight designed for use in all markets. It features a tail cap switch, momentary or constant on operation, high and low beams, a combination pocket/hat clip for convenience, and amazing brightness and run time for a light of its size and price. The aluminum housing with Type II Military Spec anodizing helps make the light extremely durable and abrasion resistant. To charge the light, slide the head cover forward to expose the micro USB port.

CASE MATERIAL: Machined aluminum alloy case. Type II MIL-Spec anodized finish. Available in Black.

DIMENSIONS: Length: 3.87 in. (98.2 mm) Body Diameter: 0.61 in. (15.6 mm)

WEIGHT: 1.20 oz. (34.1 grams) with battery (included with purchase).

LENS: Unbreakable polycarbonate lens.

LIGHT SOURCE: C4® LED technology, impervious to shock with a 30,000 hour lifetime.

LIGHT OUTPUT: High: 1150 candela peak beam intensity, 68 meter beam distance and 250 lumens measured system output.
 Low: 250 candela peak beam intensity, 31 meter beam distance and 50 lumens measured system output.



ON/OFF: Push button tail switch - momentary or constant on operation.

RUN TIME: High: 1.5 hours of run time. Low 3.5 hours of run time. All runtime claims are to 10% of initial lumen output.



BATTERY: One (1) 350 mAh Streamlight Lithium Ion cell with on board safety circuit. Rechargeable up to 300 times.

Fully recharges battery in 4.0 hours and charges battery in product. Charge indication LED: Red - Charging; Green - Charged.

FEATURES:



C4® LED technology for extreme brightness.
 IPX4 rated for water resistant operation. All openings o-ring sealed.
 1 meter impact resistance tested.
 Removable pocket/hat clip.

APPROVALS: **CE** Meets applicable European Community Directives.

BC CEC Compliant

WARRANTY: Streamlight's Limited Lifetime Warranty

OPTIONAL

ACCESSORIES: USB/AC adaptor(s).

	FL 1 STANDARD	HIGH	LOW
OUTPUT	250 LUMENS	250 LUMENS	50 LUMENS
RUNTIME	1.5h	1.5h	3.5h
DISTANCE	68m	68m	31m
INTENSITY	1,150cd	1,150cd	250cd

PERFORMANCE CURVE

