



ProTac® Rail Mount HL-X Laser
HIGH LUMEN RAIL MOUNTED STROBING TACTICAL LIGHT WITH RED LASER

MARKET

APPLICATIONS: Law Enforcement, Security, Military, Home Defense, Sporting Goods, Consumer

DESCRIPTION: Unique Gun-Mounted Tactical Light with a combination of features. Integrating an aiming laser with the white LED illuminator, it represents the latest in close combat/defense illumination technology for rifles, carbines and submachine guns. It also incorporates the versatility to use two lithium battery types; two CR123A batteries, or one Streamlight Rechargeable Li Ion cell. The light provides 1 hour 15 minutes of continuous run time on high and over 20 hours on low intensity. Rail clamp designed to rapidly and securely attach/detach from any weapon with a MIL Standard 1913 Rail.

CASE MATERIAL: 6000 Series machined aircraft aluminum with Type II Mil-Spec anodized finish. Available in Black.

DIMENSIONS: Length: 6.56 in. (16.7 cm) Width: 1.47 in. (3.73 cm) Height: 1.76 in. (4.47 cm)

WEIGHT: 10.3 oz (292.0 grams) with CR123A batteries.
10.8 oz (306.2 grams) with 18650 Li Ion rechargeable battery.

LENS: High temperature, shock mounted, AR coated, impact resistant Boro Float glass.

LIGHT SOURCE: C4® LED technology, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT: High: 18,200 candela peak beam intensity, 270m beam distance, 1000 lumens measured system output.
Low: 1,100 candela peak beam intensity, 66m beam distance, 60 lumens measured system output.
Solid-state current regulation for consistent illumination level and the reflector produces a concentrated beam with optimum peripheral illumination.

ON/OFF: Multi-function, push-button tactical tail switch or Dual remote pressure switch with latching push button. One handed operation of momentary, variable intensity or strobe mode. TEN-TAP® programmable switch allows user selection of one of three different programs: high/strobe (factory default), high only, or low/high.

RUN TIME: CR123A - High: 3/4 hour of regulated run time and one hour 15 minutes to 10% output.
Low: 17 hours of regulated run time and 20 hours to 10% output.
18650 - High: One hour 15 minutes of regulated run time and one and a half hours to 10% output.
Low: 22 hours of regulated run time and 23 hours to 10% output.

BATTERY: Two (2) 3 Volt CR123A lithium batteries, with a storage life of 10 years.
One (1) Streamlight Li Ion 18650 protected cylindrical 3.7V 2600 mAh rechargeable battery.

FEATURES: C4®LED technology for extreme brightness.
Momentary/steady On-Off switches.
One handed on/off & tighten interface keeps hands away from muzzle when attaching/detaching.
Unique clamp design allows Windage and Elevation screws to be in the proper orientation for laser sighting in any mounted position.
Mounts directly to guns with MIL-STD-1913 (Picatinny) rails.
Extensively live-fire tested, impact resistant construction.
Operating temperature: -20°F to +120°F.
IPX4 rated with the Standard two button switch or the Remote Pressure Switch installed for water resistant operation.
Serialized for positive identification.

APPROVALS: Meets applicable European Community Directives. 

WARRANTY: Streamlight's Limited Lifetime Warranty.

OPTIONAL ACCESSORIES: None