

TLR™ RM 1/TLR™ RM 2
COMPACT RAIL MOUNTED TACTICAL LIGHT

MARKET

APPLICATIONS: Law Enforcement, Security, Sporting Goods, Consumer

DESCRIPTION: Lightweight & compact, the TLR™ RM 1 and TLR™ RM 2 Weapon-Mounted Tactical Lights features the latest in shock-proof LED technology for high lumen operation. The TLR™ RM 1 provides 1.5 hours of runtime from a single CR123 lithium battery delivers 500 lumens output. The TLR™ RM 2 provides 1.5 hours of runtime with two CR123 lithium batteries featuring 1000 lumens output. Both models delivers a powerful beam with extensive range, good peripheral coverage and a selectable strobe mode. Ergonomically friendly multi-function tactical tail switch. Remote switch input option (remote switch included with purchase). Securely attach/detach from any long gun with a MIL Standard 1913 Rail.

CASE MATERIAL: Body and Facecap: 6000 Series machined aircraft aluminum with Type II Mil-Spec anodized finish. Available in Black.
Switch housing: Impact and chemical resistant Hi-impact engineered polymer.

DIMENSIONS: TLR™ RM 1 Width: 1.18 in. (2.98 cm), Height: 1.27 in. (3.22 cm), Length: 3.20 in. (8.12 cm)
TLR™ RM 2 Width: 1.18 in. (2.98 cm), Height: 1.27 in. (3.22 cm), Length: 4.55 in. (11.55 cm)

WEIGHT: TLR™ RM 1 2.74 oz. (77.9 grams) with battery (included with purchase)
TLR™ RM 2 4.55 oz. (129.0 grams) with batteries (included with purchase)

LENS: High temperature, shock mounted, AR coated, impact resistant Borofloat® glass.

LIGHT SOURCE: LED, white, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT: TLR™ RM1 500 lumens, 5,000 candela peak beam intensity and 140 m beam distance.
TLR™ RM2 1000 lumens, 10,000 candela peak beam intensity and 200 m beam distance.
Custom TIR optic produces a concentrated beam with optimum peripheral illumination.
Optimized electronics provide regulated intensity.

ON/OFF: Multi-function, push button tactical tail switch or remote pressure switch. Quick press for constant on operation and press and hold for momentary operation. Double tap either switch within ¼ second activates strobe (if enabled).
TLR™ RM 1 and TLR™ RM 2 offers “safe” mode to prevent unintentional activation. Loosen the facecap approximately ¼ turn to detent.

RUN TIME: TLR™ RM 1 1.5 continuous hours to the 10% output level. 3 continuous hours on strobe.
TLR™ RM 2 1.5 continuous hours to the 10% output level. 3 continuous hours on strobe.

BATTERY: TLR™ RM 1 one (1) 3 Volt CR123A lithium battery, with a storage life of 10 years.
TLR™ RM 2 two (2) 3 Volt CR123A lithium batteries, with a storage life of 10 years.

FEATURES: High power LED for extreme brightness.
Ambidextrous operation.
One handed snap-on and tighten interface keeps hands away from muzzle when attaching or detaching.
Securely fits a broad range of weapons using key kit provided.
Extensively live-fire tested.
Operating temperature: -40° F to +120° F.
IPX7 rated design; waterproof to 1 meter for 30 minutes.
Serialized for positive identification.

APPROVALS:  Meets applicable European Community Directives.

WARRANTY: Streamlight's Limited lifetime warranty.

OPTIONAL

ACCESSORIES: Mounting Adapters, Remote Switches.